

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims

1. (Canceled)

2. (Currently amended) In a fuel injection device, having an injection valve, having a line that supplies highly pressurized fuel to the injection valve during operation, and having a control valve that controls the pressure in a control chamber of the injection valve, which chamber is connected to the above-mentioned line, and whose moving valve element is actuatable by an actuator via a hydraulic coupler that has two pistons that cooperate with a coupler volume of the coupler, the seat of the moving valve element having an inner cross-sectional surface area f_3 and with means for filling the coupler volume with pressurized fuel via guidance gaps of the pistons,

the improvement wherein the pistons are situated one inside the other in parallel fashion; a booster chamber situated at the ends of the pistons oriented away from the actuator; a filling chamber inside the outer piston, the filling chamber being connected to said line **by means of an annular groove via a conduit in the outer piston**; one of the pistons having a piston surface area f_4 being mechanically coupled to the actuator by means of a rod that has a cross-sectional surface area f_5 ; the other piston, which has a piston area f_2 , actuating the control valve by means of a rod that has a cross-sectional area f_1 that is smaller than f_2 ; the direction of the closing movement of the moving valve element coinciding with the direction of fuel flowing out of the control chamber so that the control valve is at least partially force-balanced due to the pressure acting on the other piston in the filling chamber.